



NOTES:

1. THIS DRAWING DEFINES THE OVERALL GEOMETRY AND PERFORMANCE SPECIFICATIONS OF THE PART/ASSEMBLY, AND CONSTITUTES THE ACCEPTANCE CRITERIA THEREOF. ONLY THE ITEM(S) DESCRIBED IN THIS DOCUMENT PROCURED FROM THE VENDOR AND/OR MANUFACTURER LISTED HEREON ARE APPROVED FOR USE. A SUBSTITUTE ITEM SHALL NOT BE USED WITHOUT PRIOR APPROVAL. CONFORMANCE OF HARDWARE TO THESE REQUIREMENTS IS ACCEPTABLE IN LIEU OF VENDOR AND/OR MANUFACTURER DOCUMENTATION.

REV	ECO	DATE	DESCRIPTION	BY	APR	CHK
A	1	12/20/2018	ADDED -4 AND PAGE 2	CMK	CMK	LS
A	2	11/15/2019	ADDED -5 AND PAGE 3	CMK	CMK	LS

ACCEPTED MFR'R: NTE ELECTRONICS, INC.
44 FARRAND ST.
BLOOMFIELD, NJ 07003
(800)-631-1250

DASH NO.	MFR'R P/N	RATING	OPERATING TEMPERATURE RANGE	DIAMETER (A)	LENGTH (B)
-1	NTE125	1 AMPS, 1000 VOLTS	-65 C TO 175 C.	Ø0.107 MAX	0.210 MAX
-2	NTE576	5 AMPS, 400 VOLTS	-65 C TO 150 C.	Ø0.250 MAX	0.371 MAX
-3	NTE6084	35 AMPS, 45 VOLTS	-55 C TO 150 C.	N/A	N/A






-CONFIDENTIAL INFORMATION-
THE INFORMATION AND DATA CONTAINED HEREIN IS PROPRIETARY AND IS SUBMITTED IN CONFIDENCE; AND SHALL NOT BE DISCLOSED, USED OR DUPLICATED FOR ANY PURPOSE WHATSOEVER WITHOUT THE PRIOR WRITTEN PERMISSION OF PARAVION TECHNOLOGY, INC.

PROTO
N/C

Paravion® Inc.		TITLE		DRAWING NO.	
Technology		DIODE		ES50191	
DIMENSIONS IN INCHES		DRAWN BY	APRVD BY	CHK'D BY	DATE
TOLERANCES EXCEPT WHERE NOTED:		EW	JT	LS	08/28/17
ECO		DO NOT SCALE DRAWING		REV A	ECO 2
ANGLES = ± 1°		© 2017 PARAVION TECH., INC. PARAVION IS A TRADEMARK OF PARAVION TECHNOLOGY, INC.		SHEET 1 OF 3	

ACCEPTED MFR'R: MICROSEMI CORPORATION
ONE ENTERPRISE
ALISO VIEJO, CA
(800) 713-4113

DASH NO.	MFR'R P/N	RATING	OPERATING TEMPERATURE RANGE
-4	APT30D60BCAG	27 AMPS, 600 VOLTS PER DIODE	-55 C TO 150 C.



Dimensions in Millimeters and (Inches)

-CONFIDENTIAL INFORMATION-
THE INFORMATION AND DATA CONTAINED HEREIN
IS PROPRIETARY AND IS SUBMITTED IN CONFIDENCE;
AND SHALL NOT BE DISCLOSED, USED OR DUPLICATED
FOR ANY PURPOSE WHATSOEVER WITHOUT THE PRIOR
WRITTEN PERMISSION OF PARAVION TECHNOLOGY, INC.


PROTO

N/C

Paravion® Technology Inc.		TITLE DIODE		DRAWING NO. ES50191	
DIMENSIONS IN INCHES TOLERANCES EXCEPT WHERE NOTED:		DRAWN BY EW	APRVD. BY JT	CHK'D BY LS	DATE 08/28/17
.X = ± .1 .XX = ± .05 .XXX = ± .010		ECO		REV A	ECO 2
ANGLES = ± 1°		DO NOT SCALE DRAWING		SHEET 2 OF 3	
		© 2018 PARAVION TECH., INC. PARAVION IS A TRADEMARK OF PARAVION TECHNOLOGY, INC.			

ACCEPTED MFR'R: VISHAY ELECTRONICS

DASH NO.	MFR'R P/N	RATING	OPERATING TEMPERATURE RANGE
-5	VS-40HF40	40 AMPS, 400 VOLTS PER DIODE	-65 C TO 190 C.



—CONFIDENTIAL INFORMATION—
THE INFORMATION AND DATA CONTAINED HEREIN
IS PROPRIETARY AND IS SUBMITTED IN CONFIDENCE;
AND SHALL NOT BE DISCLOSED, USED OR DUPLICATED
FOR ANY PURPOSE WHATSOEVER WITHOUT THE PRIOR
WRITTEN PERMISSION OF PARAVION TECHNOLOGY, INC.

PROTO

N/C

Paravion® Technology Inc.		TITLE DIODE		DRAWING NO. ES50191	
DIMENSIONS IN INCHES TOLERANCES EXCEPT WHERE NOTED:		DRAWN BY EW	APRVD. BY JT	CHK'D BY LS	DATE 08/28/17
.X = ± .1 .XX = ± .05 .XXX = ± .010		ECO		REV A	ECO 2
ANGLES = ± 1°		DO NOT SCALE DRAWING		SHEET 3 OF 3	
		© 2018 PARAVION TECH., INC. PARAVION IS A TRADEMARK OF PARAVION TECHNOLOGY, INC.			